



INCLUDED ITEMS		QTY
ITEM	DESCRIPTION	
1		0
2	PR-D-30H-XX-(XX) MOTOR SHAFT FIXING BRACKET - SPECIFY AT TIME OF ORDER	1

PR-AD-48-xxx-xxZxGQ	
TUBE DIA	48.6 mm
INTERLOCK	DUAL GROOVE
MOTOR END	NON THREADED HEX SHAFT
IDLER END	SPRING LOADED HEX
CONNECTOR	JST (S) OR M8 (M)

Unless otherwise specified upon order, Customer
 (A) Required Clearance is automatically set to 2 mm by
 Pulseroller USA Order Entry System

xxx = RL in mm
 xx = Speed Code



PULSEROLLER
 WEB: WWW.PULSEROLLER.COM
 SUPPORT: SUPPORT@PULSEROLLER.COM
 SALES: SALES@PULSEROLLER.COM

REV.	DATE	DESCRIPTION
A	20-MAY-2020	UPDATED DIMENSIONS TO METRIC
B	15-DEC-2020	ADDED CUSTOMER REQUIRED CLEARANCE
C	06-JUL-2021	ADDED DESCRIPTION CHART AND FIXING BRACKET
D	24-JAN-2023	COMBINED JST AND A1 TO ONE DWG. UPDATED DWG NUMBER

REV.	DATE	DESCRIPTION
A	20-MAY-2020	UPDATED DIMENSIONS TO METRIC
B	15-DEC-2020	ADDED CUSTOMER REQUIRED CLEARANCE
C	06-JUL-2021	ADDED DESCRIPTION CHART AND FIXING BRACKET
D	24-JAN-2023	COMBINED JST AND A1 TO ONE DWG. UPDATED DWG NUMBER

TITLE	DATE	DESIGNED BY	CHECKED BY	SCALE	SHEET
STANDARD 48 DIA DUAL GROOVE PART NUMBER PR-AD-48-xxx-xxZxGQ	21-MAR-2014			NONE	1 OF 1

FOR	DWG. NO.	REV.
SENERGY MOTOR ROLLER PULSEROLLER STANDARDS	PR-AD-48-xxx-xxZxGQ	D